



(800) 662-4263

www.optigripwalksurface.com

F-STYLE OPTIGRIP WALK SURFACE **LOAD TABLE**
 14 GA SST, 1.50" Depth

| 3-ROW / 4.71" WIDTH | | | | | | | | | | | | | |
|---------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | SPAN | | | | | | | | | | | | |
| | 2'-0" | 2'-6" | 3'-0" | 3'-6" | 4'-0" | 4'-6" | 5'-0" | 5'-6" | 6'-0" | 6'-6" | 7'-0" | 7'-6" | 8'-0" |
| U | 693 | 443 | 308 | 226 | 173 | 173 | 110 | 91 | | | | | |
| D | 0.045 | 0.071 | 0.102 | 0.139 | 0.182 | 0.231 | 0.285 | 0.345 | | | | | |
| C | 693 | 554 | 462 | 396 | 346 | 308 | 277 | 252 | 231 | 213 | 198 | | |
| D | 0.036 | 0.057 | 0.082 | 0.111 | 0.146 | 0.184 | 0.228 | 0.276 | 0.328 | 0.385 | 0.447 | | |

| 5-ROW / 7.08" WIDTH | | | | | | | | | | | | | |
|---------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | SPAN | | | | | | | | | | | | |
| | 2'-0" | 2'-6" | 3'-0" | 3'-6" | 4'-0" | 4'-6" | 5'-0" | 5'-6" | 6'-0" | 6'-6" | 7'-0" | 7'-6" | 8'-0" |
| U | 713 | 456 | 317 | 233 | 178 | 141 | 114 | 94 | 79 | | | | |
| D | 0.043 | 0.068 | 0.097 | 0.133 | 0.174 | 0.220 | 0.272 | 0.329 | 0.391 | | | | |
| C | 713 | 571 | 475 | 407 | 356 | 317 | 285 | 259 | 237 | 219 | 203 | 190 | |
| D | 0.034 | 0.054 | 0.078 | 0.106 | 0.139 | 0.176 | 0.217 | 0.263 | 0.313 | 0.368 | 0.426 | 0.486 | |

| 7-ROW / 9.46" WIDTH | | | | | | | | | | | | | |
|---------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | SPAN | | | | | | | | | | | | |
| | 2'-0" | 2'-6" | 3'-0" | 3'-6" | 4'-0" | 4'-6" | 5'-0" | 5'-6" | 6'-0" | 6'-6" | 7'-0" | 7'-6" | 8'-0" |
| U | 722 | 462 | 321 | 235 | 180 | 142 | 115 | 95 | 80 | | | | |
| D | 0.042 | 0.066 | 0.095 | 0.130 | 0.170 | 0.215 | 0.266 | 0.322 | 0.383 | | | | |
| C | 722 | 577 | 481 | 412 | 361 | 321 | 288 | 262 | 240 | 222 | 206 | 192 | |
| D | 0.034 | 0.053 | 0.076 | 0.104 | 0.136 | 0.172 | 0.213 | 0.258 | 0.307 | 0.360 | 0.418 | 0.479 | |

| 9-ROW / 11.83" WIDTH | | | | | | | | | | | | | |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| | SPAN | | | | | | | | | | | | |
| | 2'-0" | 2'-6" | 3'-0" | 3'-6" | 4'-0" | 4'-6" | 5'-0" | 5'-6" | 6'-0" | 6'-6" | 7'-0" | 7'-6" | 8'-0" |
| U | 601 | 384 | 267 | 196 | 150 | 118 | 96 | 79 | 66 | | | | |
| D | 0.041 | 0.065 | 0.093 | 0.127 | 0.166 | 0.210 | 0.260 | 0.314 | 0.374 | | | | |
| C | 601 | 480 | 400 | 343 | 300 | 267 | 240 | 218 | 200 | 184 | 171 | 160 | 150 |
| D | 0.033 | 0.052 | 0.074 | 0.101 | 0.133 | 0.168 | 0.208 | 0.251 | 0.299 | 0.351 | 0.407 | 0.468 | 0.532 |

U = safe uniform load in lb/sq-ft. Ex: Pedestrian traffic, multiple container stacks.
 C = safe concentrated load in lb/ft at mid span. Ex: Equipment legs, single container stack.
 D = deflection in inches.